

FIRE ATTACK

Trash line will only be used for miscellaneous items such as wash downs, grass fields, dumpsters, etc., and are not to be used for interior fire attack, where there is a large amount of fire.

Minimum accepted attack line for interior firefighting will be a 1-3/4" jiffy line.

Minimum accepted attack lines for interior firefighting in a commercial building, condominiums, or apartments will be a 1-3/4" jiffy line with 5" back-up lines.

IF FIRE IS CONFIRMED PRIOR TO ARRIVAL ON A RESIDENTIAL OR COMMERCIAL FIRE, OR THERE IS VISIBLE FIRE OR HEAVY SMOKE ON APPROACH TO SCENE, A 5" SUPPLY LINE WILL BE LAID ON YOUR WAY IN.

Vehicle fires with visible flame or heavy smoke on arrival will be attacked with a crosslay may be considered.

All cross lays will be loaded with 1-3/4" hose only. The Lead-off line will be loaded with 100' of 1-3/4" hose and 800' of 2-1/2" hose.

Initial fire attack and investigations should be done by Engine Company Captain along with leadoff firefighter & discharge firefighter if a supply line is not being laid or if unit is not needed in ladder operations.

Initial fire attack should be done by Engine Company Captain along with leadoff firefighter if a supply line is being laid. Discharge firefighter will assist with 5" supply line hook up and then immediately contact the fire ground commander for further instructions.

Initial fire attack should be done by Engine Company Captain along with leadoff firefighter if unit is being placed in ladder operations. Discharge firefighter will assist with setting up ladder for operations. The Driver will become the turntable operator. The Captain & the leadoff firefighter will assume the position in the basket and operator as soon as practical

Discharge firefighter are only to stay with engineer if needed for supply line hook up or ladder operations.